



Aug 2009

Packaging Details – Non Composite Products¹

Nominal Thickness	Bundle		Truckload		Weight ²	
	Pieces	SqFt ³	Pieces	SqFt ³	Lbs per Sqft	Lbs per Piece ³
0.5	96	3,072	2,304	73,728	0.08	2.7
0.625	76	2,432	1,824	58,368	0.10	3.3
0.75	64	2,048	1,536	49,152	0.13	4.0
1	48	1,536	1,152	36,864	0.17	5.3
1.1	43	1,376	1,032	33,024	0.18	5.9
1.2	40	1,280	960	30,720	0.20	6.4
1.25	38	1,216	912	29,184	0.21	6.7
1.3	36	1,152	864	27,648	0.22	6.9
1.4	34	1,088	816	26,112	0.23	7.5
1.5	32	1,024	768	24,576	0.25	8.0
1.6	30	960	720	23,040	0.27	8.5
1.7	28	896	672	21,504	0.28	9.1
1.75	27	864	648	20,736	0.29	9.3
1.8	26	832	624	19,968	0.30	9.6
1.9	25	800	600	19,200	0.32	10.1
2	24	768	576	18,432	0.33	10.7
2.1	22	704	528	16,896	0.35	11.2
2.2	21	672	504	16,128	0.37	11.7
2.25	21	672	504	16,128	0.38	12.0
2.3	20	640	480	15,360	0.38	12.3
2.4	20	640	480	15,360	0.40	12.8
2.5	19	608	456	14,592	0.42	13.3
2.6	18	576	432	13,824	0.43	13.9
2.7	17	544	408	13,056	0.45	14.4
2.75	17	544	408	13,056	0.46	14.7
2.8	17	544	408	13,056	0.47	14.9
2.9	16	512	384	12,288	0.48	15.5
3	16	512	384	12,288	0.50	16.0
3.1	15	480	360	11,520	0.52	16.5
3.2	15	480	360	11,520	0.53	17.1
3.25	14	448	336	10,752	0.54	17.3
3.3	14	448	336	10,752	0.55	17.6
3.4	14	448	336	10,752	0.57	18.1
3.5	13	416	312	9,984	0.58	18.7
3.6	13	416	312	9,984	0.60	19.2
3.7	12	384	288	9,216	0.62	19.7
3.75	12	384	288	9,216	0.63	20.0
3.8	12	384	288	9,216	0.63	20.3
3.9	12	384	288	9,216	0.65	20.8
4	12	384	288	9,216	0.67	21.3
4.5	10	320	240	7,680	0.75	24.0

¹ Durasheath-3, Eco-Max, Multi-Max FA-3, R-Matte Plus-3, Re-Cover Board-3, Thermasheath-3, Thermo-roof Plus-3, TSA-FA-3, TSP-3, TSX-8500, TSX-8510 and Ultra-Max where applicable.

² All bundles are approximately 250 lbs.

³ Data is based on 48" x 96" pieces.

⁴ 1/2"-5/8"-3/4" are sold as full bundles, but typically packaged in half packs.



Aug 2009

Packaging Details – Nailable Base-3

Nominal Thickness ¹	Bundle		Truckload		Weight		
	Pieces	SqFt ²	Pieces	SqFt ²	Lbs per Bdl ²	Lbs per Sqft	Lbs per Piece ²
1.5	32	1,024	768	24,576	1,771	1.73	55.3
1.6	30	960	720	23,040	1,676	1.75	55.9
1.7	28	896	672	21,504	1,579	1.76	56.4
1.75	27	864	648	20,736	1,530	1.77	56.7
1.8	26	832	624	19,968	1,480	1.78	56.9
1.9	25	800	600	19,200	1,437	1.80	57.5
2	24	768	576	18,432	1,392	1.81	58.0
2.1	22	704	528	16,896	1,288	1.83	58.5
2.2	21	672	504	16,128	1,240	1.85	59.1
2.25	21	672	504	16,128	1,246	1.85	59.3
2.3	20	640	480	15,360	1,192	1.86	59.6
2.4	20	640	480	15,360	1,203	1.88	60.1
2.5	19	608	456	14,592	1,153	1.90	60.7
2.6	18	576	432	13,824	1,102	1.91	61.2
2.7	17	544	408	13,056	1,049	1.93	61.7
2.75	17	544	408	13,056	1,054	1.94	62.0
2.8	17	544	408	13,056	1,059	1.95	62.3
2.9	16	512	384	12,288	1,005	1.96	62.8
3	16	512	384	12,288	1,013	1.98	63.3
3.1	15	480	360	11,520	958	2.00	63.9
3.2	15	480	360	11,520	966	2.01	64.4
3.25	14	448	336	10,752	905	2.02	64.7
3.3	14	448	336	10,752	909	2.03	64.9
3.4	14	448	336	10,752	917	2.05	65.5
3.5	13	416	312	9,984	858	2.06	66.0
3.6	13	416	312	9,984	865	2.08	66.5
3.7	12	384	288	9,216	805	2.10	67.1
3.75	12	384	288	9,216	808	2.10	67.3
3.8	12	384	288	9,216	811	2.11	67.6
3.9	12	384	288	9,216	818	2.13	68.1
4	12	384	288	9,216	824	2.15	68.7
4.1	11	352	264	8,448	761	2.16	69.2
4.2	11	352	264	8,448	767	2.18	69.7
4.25	11	352	264	8,448	770	2.19	70.0
4.3	11	352	264	8,448	773	2.20	70.3
4.4	10	320	240	7,680	708	2.21	70.8
4.5	10	320	240	7,680	713	2.23	71.3

¹ Includes 7/16" OSB.

² Data is based on 48" x 96" pieces.



Aug 2009

Packaging Details – Vented Nailable Base-3							
Nominal Thickness ¹	Bundle		Truckload		Weight		
	Pieces	SqFt ²	Pieces	SqFt ²	Lbs per Bdl ²	Lbs per Sqft	Lbs per Piece ²
2.2	21	672	504	16,128	1,480	2.20	70.5
2.3	20	640	480	15,360	1,420	2.22	71.0
2.4	20	640	480	15,360	1,431	2.24	71.6
2.5	19	608	456	14,592	1,370	2.25	72.1
2.6	18	576	432	13,824	1,307	2.27	72.6
2.7	17	544	408	13,056	1,244	2.29	73.2
2.8	17	544	408	13,056	1,253	2.30	73.7
2.9	16	512	384	12,288	1,187	2.32	74.2
3	16	512	384	12,288	1,196	2.34	74.8
3.1	15	480	360	11,520	1,129	2.35	75.3
3.2	15	480	360	11,520	1,137	2.37	75.8
3.3	14	448	336	10,752	1,069	2.39	76.4
3.4	14	448	336	10,752	1,076	2.40	76.9
3.5	13	416	312	9,984	1,006	2.42	77.4
3.6	13	416	312	9,984	1,013	2.44	78.0
3.7	12	384	288	9,216	942	2.45	78.5
3.8	12	384	288	9,216	948	2.47	79.0
3.9	12	384	288	9,216	955	2.49	79.6
4	12	384	288	9,216	961	2.50	80.1
4.1	11	352	264	8,448	887	2.52	80.6
4.2	11	352	264	8,448	893	2.54	81.2
4.3	11	352	264	8,448	899	2.55	81.7
4.4	10	320	240	7,680	822	2.57	82.2
4.5	10	320	240	7,680	828	2.59	82.8
4.6	10	320	240	7,680	833	2.60	83.3
4.7	10	320	240	7,680	838	2.62	83.8
4.8	10	320	240	7,680	844	2.64	84.4
4.9	9	288	216	6,912	764	2.65	84.9
5	9	288	216	6,912	769	2.67	85.4
5.1	9	288	216	6,912	774	2.69	86.0
5.2	9	288	216	6,912	778	2.70	86.5

¹ Includes 7/16" OSB and 3/4" air space (furring strips).

² Data is based on 48" x 96" pieces.



Aug 2009

Packaging Details – Mult-Vent Nailable Base-3

Nominal Thickness ¹	Bundle		Truckload		Weight		
	Pieces	SqFt ²	Pieces	SqFt ²	Lbs per Bdl ²	Lbs per Sqft	Lbs per Piece ²
2.2	21	672	504	16,128	1,283	1.91	61.1
2.3	20	640	480	15,360	1,232	1.93	61.6
2.4	20	640	480	15,360	1,243	1.94	62.2
2.5	19	608	456	14,592	1,191	1.96	62.7
2.6	18	576	432	13,824	1,138	1.98	63.2
2.7	17	544	408	13,056	1,084	1.99	63.8
2.8	17	544	408	13,056	1,093	2.01	64.3
2.9	16	512	384	12,288	1,037	2.03	64.8
3	16	512	384	12,288	1,046	2.04	65.4
3.1	15	480	360	11,520	988	2.06	65.9
3.2	15	480	360	11,520	996	2.08	66.4
3.3	14	448	336	10,752	937	2.09	67.0
3.4	14	448	336	10,752	945	2.11	67.5
3.5	13	416	312	9,984	884	2.13	68.0
3.6	13	416	312	9,984	891	2.14	68.6
3.7	12	384	288	9,216	829	2.16	69.1
3.8	12	384	288	9,216	835	2.18	69.6
3.9	12	384	288	9,216	842	2.19	70.2
4	12	384	288	9,216	848	2.21	70.7
4.1	11	352	264	8,448	783	2.23	71.2
4.2	11	352	264	8,448	789	2.24	71.8
4.3	11	352	264	8,448	795	2.26	72.3
4.4	10	320	240	7,680	728	2.28	72.8
4.5	10	320	240	7,680	734	2.29	73.4
4.6	10	320	240	7,680	739	2.31	73.9
4.7	10	320	240	7,680	744	2.33	74.4
4.8	10	320	240	7,680	750	2.34	75.0
4.9	9	288	216	6,912	679	2.36	75.5
5	9	288	216	6,912	684	2.38	76.0
5.1	9	288	216	6,912	689	2.39	76.6
5.2	9	288	216	6,912	694	2.41	77.1

¹ Includes 7/16" OSB and 3/4" air space (blocks).

² Data is based on 48" x 96" pieces.



Aug 2009

Packaging Details – Thermaroof Composite-3

Nominal Thickness ¹	Bundle		Truckload		Weight		
	Pieces	SqFt ²	Pieces	SqFt ²	Lbs per Bdl ²	Lbs per Sqft	Lbs per Piece ²
1.5	32	1,024	768	24,576	551	0.54	17.2
1.6	30	960	720	23,040	532	0.55	17.7
1.7	28	896	672	21,504	512	0.57	18.3
1.75	27	864	648	20,736	500	0.58	18.5
1.8	26	832	624	19,968	489	0.59	18.8
1.9	25	800	600	19,200	483	0.60	19.3
2	24	768	576	18,432	477	0.62	19.9
2.1	22	704	528	16,896	449	0.64	20.4
2.2	21	672	504	16,128	440	0.65	20.9
2.25	21	672	504	16,128	445	0.66	21.2
2.3	20	640	480	15,360	429	0.67	21.5
2.4	20	640	480	15,360	440	0.69	22.0
2.5	19	608	456	14,592	428	0.70	22.5
2.6	18	576	432	13,824	415	0.72	23.1
2.7	17	544	408	13,056	401	0.74	23.6
2.75	17	544	408	13,056	406	0.75	23.9
2.8	17	544	408	13,056	410	0.75	24.1
2.9	16	512	384	12,288	395	0.77	24.7
3	16	512	384	12,288	403	0.79	25.2
3.1	15	480	360	11,520	386	0.80	25.7
3.2	15	480	360	11,520	394	0.82	26.3
3.25	14	448	336	10,752	372	0.83	26.5
3.3	14	448	336	10,752	375	0.84	26.8
3.4	14	448	336	10,752	383	0.85	27.3
3.5	13	416	312	9,984	362	0.87	27.9
3.6	13	416	312	9,984	369	0.89	28.4
3.7	12	384	288	9,216	347	0.90	28.9
3.75	12	384	288	9,216	350	0.91	29.2
3.8	12	384	288	9,216	354	0.92	29.5
3.9	12	384	288	9,216	360	0.94	30.0
4	12	384	288	9,216	366	0.95	30.5
4.1	11	352	264	8,448	342	0.97	31.1
4.2	11	352	264	8,448	348	0.99	31.6
4.25	11	352	264	8,448	351	1.00	31.9
4.3	11	352	264	8,448	354	1.00	32.1
4.4	10	320	240	7,680	327	1.02	32.7
4.5	10	320	240	7,680	332	1.04	33.2

¹ Includes 1/2" perlite.

² Data is based on 48" x 96" pieces.